

# Aqua Mix® Sealer's Choice® Gold

## 1 Product Name

Aqua Mix® Sealer's Choice® Gold

## 2 Manufacturer

Custom Building Products  
 Technical Services  
 10400 Pioneer Boulevard, Unit 3  
 Santa Fe Springs, CA 90670  
 Customer Support: 800-272-8786  
 Technical Services: 800-282-8786  
 Fax: 800- 200-7765  
 Email: [contactus@cbpmail.net](mailto:contactus@cbpmail.net)  
[custombuildingproducts.com](http://custombuildingproducts.com)

## 3 Product Description

A premium, no-sheen, natural look, water-based, penetrating sealer formulated to provide maximum stain protection, especially in food preparation and serving areas. Allows moisture vapor transmission. Rapid Cure Formula protects in less than 4 hours. May also be used as a pre-grouting sealer.

### Key Features

- Premium sealer for stone, tile and grout
- Maximum stain resistance
- Water-based formula
- For interior and exterior use

### Suitable Tile Types

As a sealer or grout release for all natural stone surfaces, unglazed tile, porcelain, clay pavers, concrete, brick, masonry, and grout. For interior and exterior use.

### Limitations to the Product

- Do not allow sealer to come in contact with any non-recommended surface.
- If product is allowed to dry on surface, a white film may form. If this occurs, scrub with [Aqua Mix NanoScrub](#) and a white nylon pad.
- Sealer will not prevent surface wear or etching from acids or caustic chemicals.

## 4 Technical Data

### Technical Properties Chart

Complies with all Federal EPA and SCAQMD standards for VOC

### Technical Chart

| Property         | Test Method | Typical Results |
|------------------|-------------|-----------------|
| Stain Resistance | CTI-072     | Excellent       |
| pH               |             | 8               |

## 5 Instructions

### General Surface Prep

Surface should be dry, clean and free of waxes, sealers or finishes. New installations need to be dry 48 hours before application. Protect surrounding surfaces. Test product in an inconspicuous area to ensure desirable results.



Exterior applications must meet moisture conditions - [read CUSTOM Technical Bulletin 49](#) for details.

### Application of Product

**USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.**

Read entire label before using. Apply using a paint pad applicator, sponge or brush. Allow it to penetrate for up to 5 minutes. Wipe surface completely dry using clean, dry cotton, paper or microfiber towels after each application. Porous surfaces may require additional applications. Conduct a test to see if surface is completely sealed after 2 hours by applying drops of water on the surface. If it penetrates, an additional application is required.

### Pre-Grout Sealer/Grout Release

Porous tile and stone can be stained by grout during installation. Sealing the tile before grouting will make grout removal much easier. Apply sealer according to directions after tile has been bonded for a minimum of 24 hours, or apply to front face of tile before installation. Wait a minimum of 2 hours before grouting.

### Drying Time

- Allow 30 minutes drying time between applications.
- Ready for surface traffic in 2 hours.
- Keep dry for 12 hours.
- Achieves a full cure in 24 hours.

### Cleaning of equipment

Clean tools with soap and water immediately after use.

### Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear appropriate skin and eye protection equipment and ventilate area when spraying. Contains glycol ether monobutyl ether. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention.



# CUSTOM®

# Aqua Mix® Sealer's Choice® Gold

## 6 Availability & Cost

| Location | Item Code | Size             | Package |
|----------|-----------|------------------|---------|
| USA      | 030881    | 1 pt (473 ml)    | Bottle  |
| USA      | 030882-4  | 1 qt (946 ml)    | Bottle  |
| USA      | 030883    | 1 gallon (3.8 L) | Bottle  |
| USA      | 030884    | 5 gallon (19 L)  | Pail    |
| Canada   | C030881   | 1 pt (473 ml)    | Bottle  |
| Canada   | C030882-4 | 1 qt (946 ml)    | Bottle  |
| Canada   | C030883   | 1 gallon (3.8 L) | Bottle  |
| Canada   | C030884   | 5 gallon (19 L)  | Pail    |

## 7 Product Warranty

Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. CUSTOM's sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with CUSTOM's printed instructions. CUSTOM makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another. This warranty is not transferrable.

## 8 Product Maintenance

Do not use cleaners containing ammonia, acids or bleach. Use an appropriate TileLab® or Aqua Mix® neutral cleaner. Tile industry experts recommend periodic testing of sealed surfaces. Apply a few drops of water on the surface. If it soaks in, an additional application of sealer will be necessary to keep sealer at peak performance.

## 9 Technical Services Information

For technical assistance, contact Custom technical services at 800-282-8786 or visit [custombuildingproducts.com](http://custombuildingproducts.com).

## 10 Filing System

Additional product information is available from the manufacturer upon request.

### VOC Content

Maximum VOCs: 73 grams per liter

### Expected Wear

- Will vary depending on hardness and texture of surface, type of area, surface wear, frequency, and type of maintenance products used
- Weather conditions, harsh cleaning methods, and high-alkaline, acidic, or solvent-based cleaners will affect wear
- Expected wear of all sealers is dependent on many environmental issues and intended use. Review our technical bulletin, TB84, at our website for more information.

## Handling & Storage

- Close container tightly after each use
- Store in original container only
- Store and use between temperatures of 45° F - 85° F (7° C - 29° C)
- Dispose of residue or any unused leftover product in accordance with applicable federal, state and local requirements

## Related Products

Aqua Mix® AquaKleen™

Aqua Mix® AquaShield™ Cleaner & Resealer

Aqua Mix® Concentrated Stone & Tile Cleaner



# Aqua Mix® Sealer's Choice® Gold

---

**Coverage**

Depends on type of stone or tile, porosity and texture of surface, temperature, humidity, and method of application.

| Size              | Min Coverage                             | Max Coverage                                |
|-------------------|--|---|
| 1 Gallon (3.78 L) | 300 ft <sup>2</sup> (28 M <sup>2</sup> ) | 1,500 ft <sup>2</sup> (139 M <sup>2</sup> ) |

