

Mapei Mapesil LM

Mapei Australia Pty Ltd

Chemwatch Hazard Alert Code: 2

Chemwatch: 5044-48

Version No: 8.1.1.1

Material Safety Data Sheet according to NOHSC and ADG requirements

Issue Date: 11/11/2015

Print Date: 29/07/2016

S.Local.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Mapei Mapesil LM
Synonyms	Silicone Silicon Joint Oxime cure sealant
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Used as a sealant and an adhesive. (VOC per CA South Coast Air Quality Management District, Rule 1168)
--------------------------	--

Details of the supplier of the safety data sheet

Registered company name	Mapei Australia Pty Ltd	Mapei New Zealand Ltd
Address	180 Viking Drive Wacol QLD 4076 Australia	30 Fisher Crescent Mt Wellington Auckland New Zealand
Telephone	+61 7 3276 5000 (Mon-Fri 8am to 5pm)	+64 9 921 1994 (Mon-Fri 9am-5pm)
Fax	+61 7 3276 5076	+64 9 921 1993
Website	www.mapei.com.au	www.mapei.co.nz
Email	sales@mapei.com.au	enquiries@mapei.co.nz

Emergency telephone number

Association / Organisation	Not Available	Not Available
Emergency telephone numbers	13 11 26	0800 POISON (0800 764 766)
Other emergency telephone numbers	Police or Fire Brigade 000	Police or Fire Brigade 111

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to NOHSC Criteria, and ADG Code.

CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability	1	2
Toxicity	0	1
Body Contact	2	3
Reactivity	1	2
Chronic	0	1

0 = Minimum
1 = Low
2 = Moderate
3 = High
4 = Extreme

Poisons Schedule	Not Applicable
Risk Phrases [1]	Not Applicable
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Not Applicable

Relevant risk statements are found in section 2

Indication(s) of danger	Not Applicable
-------------------------	----------------

SAFETY ADVICE

Not Applicable

Other hazards

May produce discomfort of the eyes and skin*.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Continued...

Mapei Mapesil LM

Mixtures

CAS No	%[weight]	Name
9016-00-6	>60	<u>poly(dimethyl siloxane)</u>
Not Available	30-60	inert fillers non regulated
Not Available	<10	oximesilane crosslinking agents
Not Available	<=2	organometallic tin catalysts
		NOTE: Air-curing results in evolution of
96-29-7		<u>methyl ethyl ketoxime</u>
67-56-1		<u>methanol</u>
		NOTE: Manufacturer has disclosed full ingredient
		information to allow CHEMWATCH assessment.

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▶ Other measures are usually unnecessary.
Ingestion	<ul style="list-style-type: none"> ▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ▶ Water spray or fog.
- ▶ Alcohol stable foam.
- ▶ Dry chemical powder.
- ▶ Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

Advice for firefighters

Fire Fighting	<ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus plus protective gloves. ▶ Prevent, by any means available, spillage from entering drains or water courses. ▶ Use water delivered as a fine spray to control fire and cool adjacent area. ▶ DO NOT approach containers suspected to be hot.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Combustible. ▶ Slight fire hazard when exposed to heat or flame. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. ▶ On combustion, may emit toxic fumes of carbon monoxide (CO). ▶ May emit acid smoke. <p>Combustion products include: carbon dioxide (CO₂) other pyrolysis products typical of burning organic material</p>

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	<p>Slippery when spilled.</p> <ul style="list-style-type: none"> ▶ Clean up all spills immediately. ▶ Avoid contact with skin and eyes. ▶ Wear impervious gloves and safety goggles. ▶ Trowel up/scrape up. ▶ Place spilled material in clean, dry, sealed container. ▶ Clean up all spills immediately. ▶ Avoid breathing vapours/ aerosols or dusts and avoid contact with skin and eyes. ▶ Place in a suitable, labelled container for waste disposal.
Major Spills	<p>Slippery when spilled. Minor hazard.</p> <ul style="list-style-type: none"> ▶ Clear area of personnel. ▶ Alert Fire Brigade and tell them location and nature of hazard.

Continued...

Mapei Mapesil LM

- ▶ Control personal contact with the substance, by using protective equipment as required.
- ▶ Prevent spillage from entering drains or water ways.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> ▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Prevent concentration in hollows and sumps. ▶ DO NOT enter confined spaces until atmosphere has been checked.
Other information	<ul style="list-style-type: none"> ▶ Store in original containers. ▶ Keep containers securely sealed. ▶ Store in a cool, dry, well-ventilated area. ▶ Store away from incompatible materials and foodstuff containers. ▶ Protect containers against physical damage and check regularly for leaks.

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> ▶ Metal can or drum ▶ Packaging as recommended by manufacturer. ▶ Check all containers are clearly labelled and free from leaks.
Storage incompatibility	<ul style="list-style-type: none"> ▶ Avoid reaction with oxidising agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA


Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	methanol	Methyl alcohol	262 mg/m ³ / 200 ppm	328 mg/m ³ / 250 ppm	Not Available	Sk

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
poly(dimethyl siloxane)	Polydimethyl siloxane; (Dimethylpolysiloxane)	0.74 mg/m ³	8.2 mg/m ³	790 mg/m ³
methyl ethyl ketoxime	Butanone oxime; (Ethyl methyl ketoxime)	10 ppm	10 ppm	52 ppm
methanol	Methyl alcohol; (Methanol)	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
poly(dimethyl siloxane)	Not Available	Not Available
inert fillers non regulated	Not Available	Not Available
oximesilane crosslinking agents	Not Available	Not Available
organometallic tin catalysts	Not Available	Not Available
methyl ethyl ketoxime	Not Available	Not Available
methanol	25,000 ppm	6,000 ppm

Exposure controls

Appropriate engineering controls	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly.</p>
Personal protection	
Eye and face protection	<ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.
Skin protection	See Hand protection below
Hands/feet protection	<ul style="list-style-type: none"> ▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber
Body protection	See Other protection below

Other protection	<ul style="list-style-type: none"> ▶ Overalls. ▶ P.V.C. apron. ▶ Barrier cream. ▶ Skin cleansing cream.
Thermal hazards	Not Available

Recommended material(s)**GLOVE SELECTION INDEX**

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Mapei Mapesil LM

Material	CPI
BUTYL	A
BUTYL/NEOPRENE	A
PE/EVAL/PE	A
PVDC/PE/PVDC	A
SARANEX-23 2-PLY	A
SARANEX-23	A
TEFLON	A
VITON/NEOPRENE	A
NEOPRENE	B
NAT+NEOPR+NITRILE	C
NATURAL RUBBER	C
NATURAL+NEOPRENE	C
NEOPRENE/NATURAL	C
NITRILE	C
PVA	C
PVC	C

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	Air-line*	AX-2 P2	AX-PAPR-2 P2 ^
up to 20 x ES	-	AX-3 P2	-
20+ x ES	-	Air-line**	-

* - Continuous-flow; ** - Continuous-flow or positive pressure demand

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Appearance	Coloured non-flowing paste; does not mix with water. Vapours released during curing may be mildly irritating.		
Physical state	Non Slump Paste	Relative density (Water = 1)	1.33
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	VOC = 50.6 g/l
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	> 1.0	VOC g/L	Not Available

Mapei Mapesil LM

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Not normally a hazard due to non-volatile nature of product
Ingestion	Silicone fluids do not have a high acute toxicity. They may have a laxative effect and produce central nervous system depression. Smoothing the sealant with saliva wet finger may introduce sealant into the mouth. Safer alternatives should replace this poor work practice. Small amounts may be highly irritating to sensitive mouth parts and in extreme cases produce small blisters but no toxic effects are known.
Skin Contact	There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Low molecular weight silicone fluids may exhibit solvent action and may produce skin irritation. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.
Eye	There is some evidence to suggest that this material can cause eye irritation and damage in some persons. Eye exposure to silicone fluids causes temporary irritation of the conjunctiva. Injection into the specific structures of the eye, however, causes corneal scarring, permanent eye damage, allergic reactions and cataract, and may lead to blindness. The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

	TOXICITY	IRRITATION
Mapei Mapesil LM	Not Available	Not Available
poly(dimethyl siloxane)	Not Available	Eye (rabbit): 100 mg/1h - mild.
methyl ethyl ketoxime	Dermal (rabbit) LD50: >184-<2 mg/kg ^[1] Inhalation (rat) LC50: 20 mg/l/4h ** ^[2] Oral (rat) LD50: >900 mg/kg ^[1]	Eye (rabbit): 0.1 ml - SEVERE
methanol	Dermal (rabbit) LD50: 15800 mg/kg ^[2] Inhalation (rat) LC50: 64000 ppm/4hr ^[2] Oral (rat) LD50: >1187-2769 mg/kg ^[1]	Eye (rabbit): 100 mg/24h-moderate Eye (rabbit): 40 mg-moderate Skin (rabbit): 20 mg/24 h-moderate

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

POLY(DIMETHYL SILOXANE)	Siloxanes may impair liver and hormonal function, as well as the lung and kidney. They have not been found to be irritating to the skin and eyes. They may potentially cause cancer (tumours of the womb in females) and may cause impaired fertility or infertility. No significant acute toxicological data identified in literature search. NOTE: Tumorigenic in rats : Neoplastic by RTECS criteria. Product subject to review for use in body implants Chronic exposure Carcinogenicity-rat-Implant Tumorigenic:Neoplastic by RTECS criteria. Lungs, Thorax, or Respiration:Tumors. Endocrine:Tumors
METHYL ETHYL KETOXIME	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested. For methyl ethyl ketoxime (MEKO): At medium to high concentrations, MEKO increased the rate of liver tumours in animal testing. This seems to be due to the breakdown of MEKO into a cancer-causing substance, and occurred more often in males. MEKO does not seem to cause mutations. Repeated exposure appeared to cause effects on the nose, spleen, liver, kidney and blood. Animal testing suggests that MEKO did not cause reproductive or developmental effects below 10mg/kg body weight/day. Mammalian lymphocyte mutagen *Huls Canada ** Merck

Mapei Mapesil LM

METHANOL	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.		
Acute Toxicity	☉	Carcinogenicity	☉
Skin Irritation/Corrosion	☉	Reproductivity	☉
Serious Eye Damage/Irritation	☉	STOT - Single Exposure	☉
Respiratory or Skin sensitisation	☉	STOT - Repeated Exposure	☉
Mutagenicity	☉	Aspiration Hazard	☉

Legend: ✘ – Data available but does not fill the criteria for classification
✔ – Data required to make classification available
☉ – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
poly(dimethyl siloxane)	BCF	72	Fish	1.33mg/L	4
methyl ethyl ketoxime	EC50	96	Algae or other aquatic plants	4.557mg/L	3
methyl ethyl ketoxime	LC50	96	Fish	37.890mg/L	3
methyl ethyl ketoxime	EC50	48	Crustacea	ca.201mg/L	2
methyl ethyl ketoxime	EC50	72	Algae or other aquatic plants	ca.6.09mg/L	2
methyl ethyl ketoxime	NOEC	72	Algae or other aquatic plants	ca.1.02mg/L	2
methanol	BCF	24	Algae or other aquatic plants	0.05mg/L	4
methanol	EC50	24	Algae or other aquatic plants	0.0246708mg/L	4
methanol	EC50	48	Crustacea	>10000mg/L	4
methanol	EC50	96	Algae or other aquatic plants	16.912mg/L	4
methanol	LC50	96	Fish	>100mg/L	4
methanol	NOEC	72	Crustacea	0.1mg/L	4

Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
methyl ethyl ketoxime	LOW	LOW
methanol	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
methyl ethyl ketoxime	LOW (BCF = 5.8)
methanol	LOW (BCF = 10)

Mobility in soil

Ingredient	Mobility
methyl ethyl ketoxime	LOW (KOC = 130.8)
methanol	HIGH (KOC = 1)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> ▶ Recycle wherever possible or consult manufacturer for recycling options. ▶ Consult State Land Waste Management Authority for disposal. ▶ Bury residue in an authorised landfill. ▶ Recycle containers if possible, or dispose of in an authorised landfill.
-------------------------------------	--

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Continued...

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

POLY(DIMETHYL SILOXANE)(9016-00-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

METHYL ETHYL KETOXIME(96-29-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

METHANOL(67-56-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Inventory of Chemical Substances (AICS)

Australia Hazardous Substances Information System - Consolidated Lists

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (methyl ethyl ketoxime; methanol; poly(dimethyl siloxane))
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	N (poly(dimethyl siloxane))
Japan - ENCS	Y
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	N (poly(dimethyl siloxane))
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

Name	CAS No
poly(dimethyl siloxane)	9016-00-6, 28323-47-9

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average
 PC – STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit,
 IDLH: Immediately Dangerous to Life or Health Concentrations
 OSF: Odour Safety Factor
 NOAEL :No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors
 BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.